



FABER CHIMICA S.R.L.
Via Dante, 254 - 60044 Fabriano (An) Italy
Tel: +39 0732.627178 Fax: +39 0732.22935
www.faberchimica.com

HIDRO PROTECTOR MM

STAIN-PROOF WATER-REPELLENT IN-DEPTH IMPREGNATOR

Description

HIDRO PROTECTOR MM is a water-based ecofriendly stain proof. Formulated to guarantee a excellent stain-proof power to natural polished materials without changing their color and to give them a high protection degree against dampness rising from the bottom. Application is recommended when it is required a strong (thanks to the product features) and long lasting (owing to its penetration power) protection. Can also be used on slightly damp surfaces and as a pretreatment to make easier the operations after setting. Applied by immersion, prevents stains due to dampness on some natural stone.



USE

Use the product undiluted uniformly and following the recommended ratio.

Use on the production plant:

On the production line the product can be applied by immersion or with sprayer and, for not specially porous materials, also sponge rolls can be used.

Pre-treatment on the job site:

Before setting or grouting apply the product to a dusted material, dry or slightly humid, by immersion, with a sprayer or a brush. The product penetrates and dries alone, but avoid any excess. Wait 24 hours at least after treatment, before setting or grouting.

Application as a water-repellent and stainproof:

As a water-repellent and stain-proof apply the product to a clean and dry or slightly damp surface with a sprayer or a brush. The product penetrates and dries easily, but avoid any excess.

Advantages

- Excellent stain proof on polished materials
- Does not change the colour shade
- Eco friendly
- Long lasting
- Not filming
- Penetrating

Where to apply

For indoor and outdoor use. Marbles and granites, as in-depth water-repellent for rough materials, as a very performing stainproof for polished.

Coverage	: 10 – 15 sq.m/lit.
Storage	: Keep the container closed and in store in cool and dry place.
Shelf Life	: 24 months in the original sealed packing and kept in a cool and dry place .
Packing	: 1 lt. bottle (12per carton) – 5 lt. (4per carton) – 10 lt. cans – 25/60 lt. drum

Technical Data

Appearance	: liquid
Odour	: Odourless
pH	: 11 - 12
Colour	: Colourless
Specific gravity (20 C)	: 1020 + 5g/lit.
VOC content (UNI EN ISO 11890-2:2007)	: <0.05%
VOC emission (Met. GEV ed. May 2010)	: N.R. (lower than quantification limits by method)

Marble & Granite Stone Care Ltd.
Rm. 903, Omega Plaza, 32 Dundas Street, Kowloon, H.K.
Tel: (852) 2391 0521 Fax: (852) 2789 1678

www.mgstonecare.com.hk