



FABER CHIMICA S.R.L.
Campo dell' Olmo - 60044 Faberiano (An) Italy
Tel: +39 0732.627178 Fax: +39 0732.22935
www.faberchimica.com

PRO TEX WB

VOC FREE Stainproof Water-Repellent Impregnator

Description

PRO TEX WB is a water base stain-proof eco-friendly and VOC FREE. Its special formulation performs excellent stainproof features on polished natural stones, where it does not change the colour shade and gives a very high water-repellent degree on unpolished materials. The product, made without solvents, has a high penetration capacity also on the most compact surfaces, guaranteeing a long-lasting protection, also resistant to possible honing or cutting processes after treatment.



USE

The product must be applied undiluted evenly and sticking to the coverage ratio.

Pre-treatment before setting : before setting or grouting, apply the product on a dust free material, dry or slightly damp, by immersion, with a sprayer or a brush, applying the product homogeneously, then even out on the surface with a lambs-wool, a brush or a pad. Penetrates and dries easily. It is recommendable not to leave any excess. In case of treatment on 6 sides, apply first on the upper surface, on the other sides after drying. Wait 24 hours at least before setting or grouting.

Superficial water-repellent stain-proof application: as a water-repellent treatment before the application of other protective or finishing products, apply on a clean and dry or slightly damp surface, with a sprayer or a brush with a uniform application. The product penetrates and dries alone. It is recommendable not to leave any excess. After drying, in case of superficial excess, remove by rinsing with water.

Advantages

- Excellent stain-proof
- Eco-friendly
- VOC FREE
- Not filming
- Excellent penetration power
- UV resistant
- Not yellowing

Where to apply

For indoor and outdoor use. Polished or rough Marbles and granites and natural stones.

Coverage	: 10 – 15 sq.m/lt.
Storage	: Keep the container closed and in store in cool and dry place.
Shelf Life	: 1 - 2 years in original sealed packing.
Packing	: 1 lt. bottle (12 per carton) – 5 lt. (4 per carton) – 10 lt. cans – 25/60 lt. drum

Technical Data

Appearance	: liquid
Odor	: Odourless
pH	: 10.8 ± 0.5
Color	: Transparent
Specific gravity (20 °C)	: $1020 \pm 5 \text{ g/lt.}$
VOC content (UNI EN ISO 11890-2:2007)	: <0.05%
VOC emission (Met. GEV ed. May 2010)	: N.R. (lower than quantification limits by method)

Marble & Granite Stone Care Ltd. - As Agent
Rm. 903, Omega Plaza, 32 Dundas Street, Kowloon, H.K.
Tel: (852) 2391 0521 Fax: (852) 2789 1678
www.mgstonecare.com.hk